



MLC 55 RS EU

Communication — host port

USB host port	USB mini B, front panel behind faceplate
USB standards	USB 2.0, low speed
IR learning frequencies	30 kHz to 300 kHz
IR learning distance	4" (10 cm) to 14" (36 cm) from the receiver
Program control	Extron MLC 55, 62 and 64 Series Configuration Program for Windows® Extron Simple Instruction Set (SIS™)

Communication — serial port

Serial control port	(1) 3.5 mm captive screw connector, 2 pole, ground pin shared with IR port, for unidirectional RS-232 control (± 5 V)
Baud rate and protocol (RS-232)	9600 (default), 19200, 38400, 57600, or 115,200 baud; 8 (default) or 7 data bits; 1 stop bit; no parity (default), or even or odd parity

Communication — IR port

IR control port	(1) 3.5 mm captive screw connector, 2 pole, ground pin shared with serial port (transmit only) TTL level (0 to 5 V) modulated infrared control from 30 kHz up to 300 kHz
-----------------	---

General

Power supply	External Input: 100-240 VAC, 50-60 Hz Output: 12 VDC, 1 A, 12 watts
Power consumption	
Device	TBD
Device and power supply	TBD
Temperature/humidity	Storage: -40 to +158 °F (-40 to +70 °C) / 10% to 90%, noncondensing Operating: +32 to +122 °F (0 to +50 °C) / 10% to 90%, noncondensing
Cooling	Convection, no vents
Thermal dissipation	
Device	TBD



1409

Device and power supply	TBD
Mounting	Wall or furniture mount Mounts in a standard 2 gang EU electrical junction box.
Mounting centers	60 mm vertical 70 mm horizontal
Enclosure type	Plastic
Enclosure dimensions	
Faceplate	3.17" H x 6.00" W x 0.44" D (8.05 cm H x 15.15 cm W x 1.12 cm D)
Device	1.82" H x 4.11" W x 1.22" D (4.62 cm H x 10.44 cm W x 3.09 cm D) Fits the opening in a standard 2 gang EU junction box. (Depth includes connectors. Allow enough depth in the junction box for device plus cable clearance.)
Product weight	TBD
Shipping weight	TBD
Vibration	ISTA 1A in carton (International Safe Transit Association)
Regulatory compliance	
Safety	CE, c-UL, UL
EMI/EMC	CE, C-tick, FCC Class A, ICES, VCCI Class A
Accessibility	Section 508 of the Rehabilitation Act (29 U.S.C. 794d)

Nur das Beste für Sie!

