



USB

USB standards	USB 2.0, USB 1.1, USB 1.0 compatible
USB data rates	Low speed (1.5 Mbps), full speed (12 Mbps), high speed (480 Mbps)
Signal transmission distance	With CAT 5/5e/6/7 cable: 450' (135 m)

USB host — Tx units

Number/signal type	1 USB (supports USB 2.0, 1.1, 1.0 speeds)
Connectors	
USB Extender Tx	1 female USB type B
USB Extender AAP Tx, USB Extender D Tx	1 female mini USB type B

Interconnection between transmitter and receiver

Connectors	1 female RJ-45 per unit
Termination standards	TIA 568A or TIA 568B
Signal transmission distance	With CAT 5/5e/6/7 cable: 450' (135 m) <i>The transmission distance varies depending on the type of cable used in the system.</i>

USB hub — Rx units

Number/signal type	(1) 4-port USB hub
Connectors	4 female USB type A

General

Power supply	External Input: 100-240 VAC, 50-60 Hz Output: 12 VDC, 1 A
Power input	
Transmitters	12 VDC, 0.4 A
Receivers	12 VDC, 1.0 A
Temperature/humidity	Storage: -40 to +158 °F (-40 to +70 °C) / 10% to 90%, noncondensing Operating: +32 to +122 °F (0 to +50 °C) / 10% to 90%, noncondensing
Cooling	
USB Extender Tx/Rx	Convection, no vents
USB Extender AAP Tx/Rx, USB Extender D Tx/Rx	Convection, vents on top
Mounting	
Rack mount	
USB Extender Tx/Rx	Yes, with optional rack shelf or rack mounting brackets



1409

USB Extender AAP Tx/Rx, USB Extender D Tx/Rx	No
Furniture or wall mount	
USB Extender Tx/Rx	Yes, with optional mounting kits
USB Extender AAP Tx/Rx	Yes, with optional mounting frame or Extron product with AAP openings
USB Extender D Tx/Rx	Wall or furniture mountable in a 1 gang Decora®-style opening
Enclosure type	Metal
Enclosure dimensions	
USB Extender Tx/Rx	1.0" H x 4.3" W x 3.0" D (quarter rack width) (2.5 cm H x 10.9 cm W x 7.6 cm D) (Depth excludes connectors.)
USB Extender AAP Tx/Rx	
Faceplate	1.4" H x 3.5" W x 0.1" D (3.5 cm H x 8.9 cm W x 0.3 cm D) (double space AAP plate)
Device	1.4" H x 2.5" W x 1.4" D (3.5 cm H x 6.4 cm W x 3.6 cm D) (Depth excludes connectors and pigtail. Allow at least 1.6" (4.1 cm) depth in the wall or furniture.)
USB Extender D Tx/Rx	
Faceplate	2.6" H* x 1.3" W x 0.1" D (6.6 cm H* x 3.3 cm W x 0.3 cm D) (Fits the opening in a 1 gang Decora®-style wallplate.) *Overall height is 4.1" (10.4 cm) including mounting tabs.
Device	1.4" H x 2.5" W x 1.4" D (3.5 cm H x 6.4 cm W x 3.6 cm D) (Depth excludes connectors and pigtail. Allow at least 1.6" (4.1 cm) depth in the wall or furniture.)
Product weight	0.25 lbs (0.1 kg)
Shipping weight	1 lb (<1 kg)
Vibration	ISTA 1A in carton (International Safe Transit Association)
Regulatory compliance	
Safety	CE, c-UL, KCC, UL
EMI/EMC	CE, C-tick, FCC Class A, ICES, VCCI Class A
Environmental	Complies with the appropriate requirements of RoHS, WEEE
Warranty	3 years parts and labor



Nur das Beste für Sie!